


SE Series

Model	Volt	Ampere	Capacity Ah		Weight KG	Three Phase 380-420Vac		Single Phase 220-255	
			10h	12h		Absorb (A)	Box	Absorb (A)	Box
SE24020	24	20	100	130	14	\	\	3,4	M
SE24030		30	140	190	16	\	\	5,1	M
SE24040		40	190	240	19	\	\	6,7	M
SE24050		50	250	315	20	\	\	8,4	M
SE24060		60	300	370	24	3	C	10,3	C
SE24070		70	320	390	25	\	\	11,8	M
SE24080		80	350	500	55	3,9	C	13,4	C
SE24100		100	430	620	58	4,9	C	16,7	C
SE24120		120	500	750	59	5,9	C	20	C
SE24140		140	600	870	63	6,9	S	23,4	C
SE24160		160	680	1000	64	7,9	S	26,8	S
SE24180		180	760	1125	75	8,8	S	\	\
SE36080		36	80	350	500	58	5,9	C	20
SE36100	100		430	620	61	7,4	C	25	C
SE36120	120		500	750	62	8,8	C	30	S
SE36140	140		600	870	66	10,3	S	35	S
SE36160	160		680	1000	73	11,8	S	40	S
SE36180	180		760	1125	88	13,3	S	\	\
SE48060	48	60	300	370	58	5,9	C	20	C
SE48080		80	350	500	61	7,8	C	27	C
SE48100		100	430	620	64	9,8	C	33,4	S
SE48120		120	500	750	73	11,8	C	40	S
SE48140		140	600	870	83	13,8	S	\	\
SE48160		160	680	1000	88	15,8	S	\	\
SE72080	72	80	350	500	72	11,8	C	40	S
SE72100		100	430	620	85	14,8	C	50	S
SE72120		120	500	750	90	17,7	S	60	S
SE80060	80	60	300	370	65	9,9	C	33,4	S
SE80080		80	350	500	72	13,1	C	44,5	S
SE80100		100	430	620	81	16,4	C	55,7	S
SE80120		120	500	750	90	19,7	S	\	\
SE80140		140	600	870	97	23	S	\	\
SE80160		160	680	1000	\	26,5	S	\	\
SE80180		180	760	1125	\	30	S	\	\

Protection IP 21, Galvanized metal to prevent deteriorating, varnished with epoxy paint.

Box "M" = 400 x 300 x 300(H) | Box "C" = 400 x 600 x 610(H) | Box "S" 400 x 600 x 900(H)



Box "M"



Box "C"



Box "S"

T.C.E. Srl

Via G. di Vittorio, 5 35046 Saletto (PD) - Italy

Tel. +39 0429 89290

E-mail info@tce-italy.it

Web. www.tcechargers.com